



Jaguar Thermostatic Radiator Valve - Corner



| Available Finishes | |
|--------------------|------------------------|
| Chrome | Brushed (Satin) Nickel |
| Antique Brass | Black Nickel |
| Antique Copper | Brass |
| Unlacquered Brass | |

| Connection Size | |
|-------------------|-------------------|
| Valve to Radiator | 1/2" BSPT |
| Valve to Pipe | 15 mm Compression |

| Allen Key size | |
|-----------------------------|------|
| To adjust Lock-Shield | SW8 |
| To fit Coupler to Radiator | SW13 |
| Allen Keys are not included | |

| Pressure Ratings | |
|--|-----------------------|
| Max Test Pressure | 16 Bar |
| Max Operating Pressure | 10 Bar |
| Max Differential Pressure | 1 Bar |
| Pressure Drop Value (Kvs) | 1.23m ³ /h |
| Kvs value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar. | |

| Flow Ratings | |
|------------------|-----------------------|
| Normal Flow Rate | 0.42m ³ /h |
| Max Flow Rate | 1.23m ³ /h |

| Temperature Ratings | |
|------------------------------|--------|
| Max Test Temperature | 100°C |
| Max Operating Temperature | 120°C |
| Temperature Adjustment Range | 7-30°C |

| Disclaimer | |
|--|--|
| All dimensions are approximate and for roughing in only. We recommend no work be carried out until the goods arrive. We can take no responsibility for errors in information supplied. | |



Jaguar Thermostatic Radiator Valve - Corner

